



XP2

Explosion-Proof High Bay Fixture

BLUECOLT[®]
LIGHTING
...beautiful light for all



DIMENSIONS



MODEL

DIMENSIONS

Fixture with Pendant Mount

Ø 9.8" x 10.8

UL844 (North American)

Class I, Division 2, Groups A, B, C, D
Class II, Division 1, Groups E, F, G
Class II, Division 2, Groups F, G
Class III

Marine

UL1598, UL1598A
ABS
Other Rating
IP 66

ATEX

II 2 G Ex mb eb IIC T4 Gb
II 2 D Ex tb IIIC T120°C Db IP66
II 3 G Ex ec IIC T3 Gc
II 2 D Ex tb IIIC T85°C Db IP66

IECEx

Ex mb eb IIC T4 Gb
Ex tb IIIC T120°C Db IP66
Ex ec IIC T3 Gc
Ex tb IIIC T85°C Db IP66

FEATURES

Bluecolt's Explosion-Proof 2 High Bay fixture is designed for extreme environments and tough conditions. It features:

- Marine-Rated Powder Coating
- Heavy Duty & High Impact Resistance
- Versatile Mounting Options

PERFORMANCE

Lumen Output:	Up to 64,000 Lumens
Wattage:	250W-400W
Efficiency:	Up to 160 Lumens/Watt
CRI:	>70
Voltage:	100-277V AC; 200-488V AC; 12-48V DC
Operating Temperature:	-40° to 131°F
Lifespan:	50,000 hours
IP Rating:	IP66
Dimming:	0-10V

PRODUCT TYPE	WATTS	CCT	LENS	MOUNTING	OPTIONS
BLXP2 = Bluecolt Lighting Explosion-Proof 2	200W 250W 300W 350W 400W	2.2K = 2200K 3K = 3000K 4K = 4000K 5K = 5000K 6K = 6000K 6.5K = 6500L 7K = 7000K	40D = 40° 60D = 60° 90D = 90° 120D = 120°	SM = Surface Mount PM = Pendant Mount TM = Stanchion Mount WM = Wall Mount	EM = Emergency Battery LS = Lamp Shade DC = DC Power HV = High Voltage
Sample Item Number: BLXP2-400W-5K-90D-SM-EM					